Philips
PAL coax cable

10 m

Male-Female White

SWV3135W

Turn up your viewing experience

with this coaxial cable

Step up to a better audio/video connection between components.

Protects against signal loss
- Copper-braided reinforced aluminium shielding

Enjoy better picture/sound quality
- 24 carat gold-plated connectors optimise signal
- High-purity copper conductor for reliable signal transfer

Easy installation
- Colour-coded connectors for instant recognition
- Plug and play for easy use

Enjoy extended durability
- Flexible PVC jacket
- Rubber strain relief
- Protective metal shell for extended durability

PHILIPS

sense and simplicity

PAL coax cable
10 m Male-Female White

SWV3135W/10

Specifications

Packaging dimensions
- Packaging dimensions (W x H x D): 19 x 28.5 x 4 cm
- Net weight: 0.45 kg
- Gross weight: 0.61 kg
- Tare weight: 0.16 kg
- EAN: 87 12581 39303 8
- Number of products included: 1
- Packaging type: Blister

Outer Carton
- Outer carton (L x W x H): 30.2 x 21 x 17.2 cm
- Net weight: 1.8 kg
- Gross weight: 2.7 kg
- Tare weight: 0.9 kg
- EAN: 87 12581 39715 9
- Number of consumer packages: 4

Highlights

Colour-coded connectors
Colour-coded connections make it easy to install your cable into the correct inputs and outputs

Flexible PVC Jacket
Flexible PVC jacket provides protection to the delicate core of the cable. It also offers extended durability and ease of installation.

Rubber strain relief
Rubber strain relief provides a secure yet flexible juncture between the cable and the plug.

Braided shielding
Copper-braided reinforced aluminium shielding protects against signal loss and interference.

Plug and play
Plug and play offers easy installation of components without time-consuming installations.

Metal shell
The metal shell protects the internal connection of the cable. It ensures durability and reliability of your connection.

24 carat gold-plated connector
24 carat gold-plated connectors ensure the best signal quality for your components.

High-purity copper
This copper conductor provides high accuracy in signal transfer with minimal resistance.

Issue date 2010-02-17
Version: 2.0.6
12 NC: 8670 000 36786
EAN: 87 12581 39303 8

© 2010 Koninklijke Philips Electronics N.V.
All Rights reserved.
Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com